



Dishwashing

ADVANCE Series - Glasswashers

GLASS WASHER, AD-21 DD

DIMENSIONS

		Article	Packed
Length	mm	470,00	630,00
Depth	mm	545,00	580,00
Height	mm	720,00	765,00
Weigth	Kg	39,00	44,00
Volumen	m3	0,18	0,25

ELECTRICITY

Electric power	KW	
230V -1+N		2x2,5+T - 20 A
230V - III		
400V - III+N		

WATER

Water consumption (lit/h)	50,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 62,00

Certificate EQNET- CE

SGS-2199-0192-1

GLASS WASHER, AD-21 DD

Made of stainless steel.

Hourly production: 2,100 pieces/h.

Electronic operation.

Wash cycles: 90"-120"-180".

Optional cold rinse at the end of cycle.

Double rotating wash and rinse systems, above and below.

Heating elements in tank and boiler.

Tank with 2 kW heating element.

Tank capacity: 15 litres.

Boiler with 2.8 KW heating element.

Water consumption: 2.5 litres/rinse.

Thermostatic temperature control: washing at 60°C and rinsing at 90°C.

Thermo stop system that guarantees minimum rinsing temperature of 85°C.

Digital wash and rinse temperature display.

Security thermostats.

Self diagnostic system.

Anti - return protection system.

Built-in automatic rinse dispenser.

Equipped with detergent dispenser.

Safety switch for door opening.

Equipped with 2 baskets, 1 supplement for saucers and 1 cutlery container.

Total Power: 3.06 kW.

Dimensions: 470 x 545 x 720 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	175	50	65		Prever Interruptor diferencial
SOFT COLD WATER	210	50	65	3/4"	Prever llave de corte en la toma
DRAIN	270	50	65	30x25	

