



Dishwashing

ADVANCE Series - Frontal

DISHWASHER, AD-64 DD

DIMENSIONS

		Article	Packed
Length	mm	600,00	700,00
Depth	mm	625,00	700,00
Height	mm	820,00	885,00
Weigth	Kg	60,00	67,00
Volumen	m3	0,31	0,39

ELECTRICITY

Electric power	KW	
230V -1+N		2x6+T - 40 A
230V - III		3x2,5+T - 25 A
400V - III+N		4x2,5+T - 20 A

WATER

Water consumption (lit/h)	54,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) 65,00

Certificate EQNET- CE

SGS-2199-0192-1

DISHWASHER, AD-64 DD

Made of stainless steel.

Hourly production: 720 dishes/hour.

Maximum diameter of dishes: Ø 32 cm.

Electronic operation.

Wash cycles: 60"-90"-180".

Double rotating wash and rinse systems, above and below.

Heating elements in tank and boiler.

Tank with 2.8 kW heating element.

Tank capacity: 25 litres.

Boiler with 6 KW heating element.

Water consumption: 2.7 litres/rinse.

Thermostatic temperature control: washing at 60°C and rinsing at 90°C.

Thermo stop system that guarantees minimum rinsing temperature of 85°C.

Digital wash and rinse temperature display.

Security thermostats.

Self diagnostic system.

Anti - return protection system.

Built-in automatic rinse dispenser.

Equipped with detergent dispenser.

Safety switch for door opening.

Adjustable legs.

Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 4 cutlery containers.

Power: 6.65 KW - 400V 3+N+E.

Dimensions: 600 x 625 x 820 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	210	50	65		Prever Interruptor diferencial
SOFT COLD WATER	305	50	65	3/4"	Prever llave de corte en la toma
DRAIN	370	50	65	30x25	

